




# Telha Metálica Ondulada 17/980

▲ Sobrecargas inferiores a 60kg/m<sup>2</sup> que devem ser evitadas

SOBRECARGAS ADMISSÍVEIS (kgf/m <sup>2</sup> )		 2 apoios kgf/m <sup>2</sup>				 3 apoios kgf/m <sup>2</sup>				 4 apoios kgf/m <sup>2</sup>			
FLECHA	Vão (m)	0.43	0.50	0.65	0.80	0.43	0.50	0.65	0.80	0.43	0.50	0.65	0.80
COBERTURAS L/120	1.10	153	183	250	320	163	194	262	332	204	243	329	417
	1.20	117	140	191	245	136	162	219	278	171	204	276	350
	1.30	91	109	149	191	115	137	186	236	145	173	234	297
	1.40	72	86	118	151	99	118	160	202	124	148	201	255
	1.50	58	69	95	122	86	102	138	175	108	129	174	221
	1.60	47	56	77	99	75	89	121	153	94	113	152	193
	1.70	38	46	63	81	66	78	106	135	83	99	134	170
	1.80	32	38	52	67	58	69	94	119	70	84	114	146
	1.90	26	32	44	56	52	62	84	106	59	70	96	123
	2.00	22	27	36	47	46	55	75	95	50	60	82	105
2.10	18	22	31	39	42	50	67	86	42	51	70	89	
FLECHA	Vão (m)	0.43	0.50	0.65	0.80	0.43	0.50	0.65	0.80	0.43	0.50	0.65	0.80
FECHAMENTOS LATERAIS L/200	1.10	90	108	148	189	163	194	262	332	190	227	310	397
	1.20	69	82	112	144	136	162	219	278	145	174	238	304
	1.30	53	64	87	111	115	137	186	236	113	136	186	237
	1.40	42	50	68	88	99	118	16	202	90	108	147	189
	1.50	33	40	54	70	85	102	138	175	72	87	119	152
	1.60	27	32	44	56	69	83	114	145	59	71	97	124
	1.70	21	26	35	46	57	68	94	120	48	58	80	102
	1.80	17	21	29	37	47	57	78	100	40	48	66	85
	1.90	14	17	24	31	40	48	65	84	34	40	55	71
	2.00	12	14	19	25	34	40	55	71	28	34	46	60
2.10	9	11	16	21	28	34	47	60	24	29	39	51	