



# Telha Trapézio 25

▲ Sobrecargas inferiores a 60kg/m<sup>2</sup> que devem ser evitadas

SOBRECARGAS ADMISSÍVEIS (kgf/m <sup>2</sup> )		2 apoios				3 apoios				4 apoios			
		kgf/m <sup>2</sup>				kgf/m <sup>2</sup>				kgf/m <sup>2</sup>			
FLECHA	Vão (m)	0.43	0.50	0.65	0.80	0.43	0.50	0.65	0.80	0.43	0.50	0.65	0.80
COBERTURAS L/120	1.40	114	135	179	224	114	135	179	224	144	170	226	281
	1.50	99	117	156	194	99	117	156	194	125	147	196	244
	1.60	86	102	136	169	86	102	136	169	109	129	171	214
	1.70	76	90	120	149	76	90	120	149	96	114	151	188
	1.80	67	80	106	132	67	80	106	132	85	101	134	167
	1.90	60	71	95	118	60	71	95	118	76	90	120	149
	2.00	54	64	85	106	54	64	85	106	68	81	108	134
	2.10	49	57	76	95	49	57	76	95	62	73	97	121
	2.20	42	50	67	84	44	52	69	86	56	66	88	110
	2.30	37	43	58	73	40	47	63	78	51	60	80	100
2.40	32	38	50	63	36	43	57	71	46	55	73	91	
FLECHA	Vão (m)	0.43	0.50	0.65	0.80	0.43	0.50	0.65	0.80	0.43	0.50	0.65	0.80
FECHAMENTOS LATERAIS L/200	1.40	104	123	164	206	114	135	179	224	144	170	226	281
	1.50	84	99	133	166	99	117	156	194	125	147	196	244
	1.60	68	81	108	135	86	102	136	169	109	129	171	214
	1.70	56	67	89	112	76	90	120	149	96	114	151	188
	1.80	47	56	74	93	67	80	106	132	85	101	134	167
	1.90	39	47	62	78	60	71	95	118	76	90	120	149
	2.00	33	39	52	66	54	64	85	106	68	81	108	134
	2.10	28	33	45	56	49	57	76	95	62	73	97	121
	2.20	24	28	38	48	44	52	69	86	53	63	84	106
	2.30	20	24	32	41	40	47	63	78	46	55	73	91
2.40	17	21	28	35	36	43	57	71	40	48	64	80	